

Transparent gloss monomeric vinyl featuring a permanent adhesive. This material has been specifically designed for digital printing on large-format inkjets and is suitable for printing with eco solvent and solvent inks as well as UV-cured inks.

## IP 2514

This monomeric vinyl, which incorporates a B1 fire rating, has been specifically designed for printing with all solvent and UV inks. It can only be used on flat surfaces and is intended for indoor and short-term outdoor applications. IP 2514 features a strong backing paper, which offers excellent lay flat properties. The product must not be wet applied - i.e. dry application only. Laminate: IP 2820-101, IP 2820-200 or IP 2830-200 (for trade shows, exhibitions, etc)

| Specifications         |   |
|------------------------|---|
| DESCRIPTION            | Monomeric vinyl                                 |
| COLOUR                 | Clear gloss                                     |
| FACE FILM THICKNESS    | 80 $\mu$  |
| ADHESIVE               | Acrylic, permanent                              |
| ADHESIVE STRENGTH      | 16N / 25mm (Finat TM 1/24h)                     |
| RELEASE PAPER          | PE-coated silicone paper, 140g / m <sup>2</sup> |
| TEMPERATURE RANGE      | -40°C to +80°C                                  |
| DURABILITY (UNPRINTED) | Up to 3 years                                   |
| FLAME RETARDANCY       | B1  |
| SHELF LIFE             | 2 years, 20°C / 50% humidity                    |

© June 2010 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.